

2-24 Tight Buffered, Aluminum Interlocking Armored Cable Riser



Features and Benefits

- Provides superior crush resistance for added protection
- Eliminates the need for inner duct or conduit thus saving installation time
- OFCR(Riser) rating allow AIA products to be installed throughout the facility

Description

TLC Tight Buffered Aluminum Interlocking Armored cable consists of PVC overall jacket, PVC inner jacket with 2 to 24 tight buffered fiber surrounded by yarn acting as a strength member.



The core is protected by a spirally-wrapped aluminum strip that offers easy installation and high crush resistance. These cables are available in OFCR rated constructions.

Application

Riser
Duct

Flame Rating

UL1666



SPECIFICATIONS

Temperature Range	Indoor	Indoor/Outdoor
Storage Temperature	-40 C to +70 C	-40 C to +70 C
Operating Temperature	-20 C to +70 C	-40 C to +70 C

Cable Characteristics	
Fiber Count	2 to 24
Strength Member	Aramid Yarn
Overall Jacket Material	Poly Vinyl Chloride
Inner Jacket Material	Poly Vinyl Chloride
Armoring Material	Aluminum

Mechanical Characteristics	Standards/ Value
Nominal Outer Diameter (2/ 4, 6/ 8, 12/ 24) mm	11.6/ 13.0/14.7/ 16.2
Bend Radius (2/ 4, 6/ 8, 12/ 24) cm	23.2/ 26.0/ 29.4/ 32.4
Weight (2/ 4/ 6/ 8/ 12/ 24) lbs/ km	266/ 303/ 313/ 364/ 388/ 443

Optical Characteristics					
Items	Single Mode	InfiniCor 300	OM2	OM3	OM4
Core Size	9 um	62.5 um	50 um	50 um	50 um
Wavelength	(1310/ 1550) nm	(850/ 1300) nm	(850/ 1300) nm	(850/ 1300) nm	(850/ 1300) nm
Max. Attenuation	(0.5/0.4) dB/ km	(3.5/ 1.5) dB/ km	(3.5/ 1.5) dB/ km	(3.5/ 1.5) dB/ km	(3.5/ 1.5) dB/ km
Bandwidth (EMB) (High Performance)	-	220 MHz @850nm	850 MHz @850nm	2000 MHz @850nm	4700 MHz @850nm
Link Length (10Gb/ s)	-	-	150 mtr	300 mtr	550 mtr

Part Numbers					
Fiber Count	Single Mode	InfiniCor 300	OM2	OM3	OM4
2, 4 and 6	S09DI/IO###NRY-AIA2	M62DI/IO###NRO-AIA2	M50DI/IO###NRA-AIA2	M50DI/IO###NRA-AIA2	M50DI/IO###NRA-AIA2
8 and 12	S09DI/IO###NRY-AIA2	M62DI/IO###NRO-AIA2	M50DI/IO###NRA-AIA2	M50DI/IO###NRA-AIA2	M50DI/IO###NRA-AIA2
24	S09DI/IO24**NRY-AIA2	M62DI/IO24**NRO-AIA2	M50DI/IO24**NRA-AIA2	M50DI/IO24**NRA-AIA2	M50DI/IO24**NRA-AIA2

Fiber Type (9/125)	**	Fiber Type (50/125)	**	Fiber Type (62.5/125)	**
SMF-28 Ultra	CZ	ClearCurve OM2	C2	InfiniCor 300	C3
SMF28e+	C	Clear Curve OM3	CG	InfiniCor 1000	C1
ClearCurve XB	CB	ClearCurve OM4	C4		
ClearCurve LBL	C7				
ClearCurve ZBL	CC				



132 Base Road
Oriskany, NY, 13424
Phone: 315-736-7384
Fax: 315-736-1927
Toll free: 1-888-571-7111
sales@thelightconnection.com
www.thelightconnection.com