

2-72 Fiber, Micro Distribution Aluminum Interlocking Armored Cable, Riser



Features and Benefits

- Provides superior crush resistance for added protection
- Eliminates the need for inner duct or conduit thus saving installation time
- OFCR(Riser) rating allow AIA products to be installed throughout the facility



Description

TLC 2 to 72 fiber Micro Distribution Aluminum Interlocking Armored cable consists of PVC overall jacket, PVC inner jacket with 2 to 72 colored fiber surrounded by aramid yarn acting as a strength member.

The core is protected by a spirally-wrapped aluminum strip that offers easy installation and high crush resistance. These cables are available in OFCR rated constructions.

Application
Riser

Flame Rating
UL1666



SPECIFICATIONS

Temperature Range

Storage Temperature	-40 C to +70 C
Operating Temperature	-20 C to +70 C

Cable Characteristics

Fiber Count	2-72
Strength Member	Aramid Yarn
Overall Jacket Material	Poly Vinyl Chloride
Inner Jacket Material	Poly Vinyl Chloride
Armoring Material	Aluminum

Mechanical Characteristics

	Value
Nominal Outer Diameter (2-12/ 24, 36/ 48/ 72) (mm)	11.6/ 13.0/ 17.45/ 19.25
Bend Radius (2-12/ 24, 36/ 48/ 72) (cm)	23.2/ 26.0/ 34.9/ 38.5
Weight (2-12/ 24/ 36/ 48/ 72) (lbs/ km)	252/ 349/ 433/ 530/ 672

Optical Characteristics

Items	Single Mode	InfiniCor 300	OM2	OM3	OM4
Core Size	9 um	62.5 um	50 um	50 um	50 um
Wavelength	(1310/ 1550) nm	(850/ 1300) nm	(850/ 1300) nm	(850/ 1300) nm	(850/ 1300) nm
Max. Attenuation	(0.5/ 0.4) dB/ km	(3.5/ 1.5) dB/ km	(3.5/ 1.5) dB/ km	(3.5/ 1.5) dB/ km	(3.5/ 1.5) dB/ km
Bandwidth (EMB) (High Performance)	–	220 MHz @850nm	850 MHz @850nm	2000 MHz @850nm	4700 MHz @850nm
Link Length (10Gb/ s)	–	–	150 mtr	300 mtr	550 mtr

Part Numbers

Fiber Count	Single Mode	InfiniCor 300	OM2	OM3	OM4
## (2 - 12)	S09MD##**NRY-Y-AIA2	M62MD##**NRO-O-AIA2	M50MD##**NRO-O-AIA2	M50MD##**NRA-A-AIA2	M50MD##**NRA-A-AIA2
## (24 - 36)	S09MD##**NRY-Y-AIA2	M62MD##**NRO-O-AIA2	M50MD##**NRO-O-AIA2	M50MD##**NRA-A-AIA2	M50MD##**NRA-A-AIA2
## (48 - 72)	S09MD##**NRY-Y-AIA	M62MD##**NRO-O-AIA	M50MD##**NRO-O-AIA	M50MD##**NRA-A-AIA	M50MD##**NRA-A-AIA

Fiber Type (9/125) **

SMF-28 Ultra	CZ
SMF28e+	C
ClearCurve XB	CB
ClearCurve LBL	C7
ClearCurve ZBL	CC

Fiber Type (50/125) **

ClearCurve OM2	C2
Clear Curve OM3	CG
ClearCurve OM4	C4

Fiber Type (62.5/125) **

InfiniCor 300	C3
InfiniCor 1000	C1



132 Base Road
Oriskany, NY, 13424
Phone: 315-736-7384
Fax: 315-736-1927
Toll free: 1-888-571-7111
sales@thelightconnection.com
www.thelightconnection.com