

Individual Tight Buffered fibers are available and are preferred in production environments because of their ease of stripping. 900µm, 800µm and 650µm buffer sizes match existing tooling and fit the vast array of today's connectors. 12 standard colors are available in all sizes and most fiber types.

FEATURES

- Ease and consistency of stripping
- 3 sizes (900µm, 800µm and 650µm) available
- Available in 12 standard colors
- Compatible with existing tooling and fits vast array of connectors

APPLICATIONS

- Data centers
- Testing environments
- Launch (pulse) boxes
- Patch cords

ALSO AVAILABLE UPON REQUEST

- Optical fibers compliant with ITU-T G.657.A/B standards

For 800mm and 650mm Tight Buffer products, a minimum order quantity applies.

SINGLEMODE OS2	Jacket Type	Diameter mm	Weight lbs/km
S09TB01CZNU "X"	PVC	.900	2
62/125 MULTIMODE OM1			
M62TB01C3NU "X"	PVC	.900	2
50/125 MULTIMODE CLEARCURVE® OM2			
M50TB01C2NU "X"	PVC	.900	2
50/125 MULTIMODE CLEARCURVE® OM3			
M50TB01CGNU "X"	PVC	.900	2
50/125 MULTIMODE CLEARCURVE® OM4			
M50TB01C4NU "X"	PVC	.900	2

When ordering, replace X with B=blue, O=orange, G=green, BR=brown, S=slate, W=white, R=red, BL=black, Y=yellow, P=purple, PK=pink, A=aqua

