

Tight Buffer



Features and Benefits



- 3 sizes (900um, 800um, and 650um) available
- Consistent 3.5 – 5 lbs-f for stripping ease
- Compatible with existing tooling and fits a vast array of connectors

Description

The Light Connection's tight buffer is composed of an optical fiber and a PVC outer jacket. All component materials meet the EU RoHS and REACH Directive standards.

TLC tight buffer is available with two PVC jacket options, (U/P), the P-buffer has a higher concentration of flame retardants in the jacket compound.

Tight buffer is available in 12 TIA standard colors or special order colors.



Application

Data centers
Testing environments
Launch (pulse) boxes
Patchcords

Flame Rating

None

SPECIFICATIONS

Temperature Range

Storage Temperature	-40 C to +70 C
Operating Temperature	0 C to +70 C

Cable Characteristics

Fiber Count	1
Outer Jacket Material	Flame Retardant PVC
Outer Jacket Color	Available in 12 TIA/EIA color standard

Physical Characteristics

Physical Characteristics	Value
Nominal Outer Diameter (mm)	0.900 / 0.800 / 0.650
Weight (lbs/km)	2.2/ 2.0/ 1.1
Minimum Bend Radius (mm) (Bend Insensitive SM)	10
Minimum Bend Radius (mm) (Bend Insensitive MM)	7.5

Optical Characteristics

Items	Single Mode	OM1	OM2	OM3	OM4
Core Size	9 um	62.5 um	50 um	50 um	50 um
Wavelength	(1310/ 1550) nm	(850/ 1300) nm	(850/ 1300) nm	(850/ 1300) nm	(850/ 1300) nm
Max. Attenuation	(0.5/ 0.4) dB/ km	(3.5/ 1.5) dB/ km	(3.5/ 1.5) dB/ km	(3.5/ 1.5) dB/ km	(3.5/ 1.5) dB/ km
Bandwidth (EMB) (High Performance)	–	220 MHz @850nm	850 MHz @850nm	2000 MHz @850nm	4700 MHz @850nm
Link Length (10Gb/ s)	–	–	150 mtr	300 mtr	550 mtr

Part Numbers

Size	Single Mode	OM1	OM2	OM3	OM4
0.900mm	S09TB01**N(U/P)+	M62TB01**N(U/P)+	M50TB01**N(U/P)+	M50TB01**N(U/P)+	M50SX01**N(U/P)+
0.800mm	S09TB01**N(U/P)+800	M62TB01**N(U/P)+800	M50TB01**N(U/P)+800	M50TB01**N(U/P)+800	M50SX01**N(U/P)+800
0.650mm	S09TB01**N(U/P)+650	M62TB01**N(U/P)+650	M50TB01**N(U/P)+650	M50TB01**N(U/P)+650	M50SX01**N(U/P)+650

B	O	G	BR
S	W	R	BL
Y	P	PK	A

Fiber Type (9/125) **

SMF-28 Ultra	CZ
SMF28e+	C
ClearCurve XB	CB
ClearCurve LBL	C7
ClearCurve ZBL	CC

Fiber Type (50/125) **

ClearCurve OM2	C2
Clear Curve OM3	CG
ClearCurve OM4	C4

Fiber Type (62.5/125) **

InfiniCor 300	C3
InfiniCor 1000	C1



UKAS is a member of Registrar of Standards (RSG) Ltd.



132 Base Road
Oriskany, NY, 13424
Phone: 315-736-7384
Fax: 315-736-1927
Toll free: 1-888-571-7111
sales@thelightconnection.com
www.thelightconnection.com